



Fall protection

AN06410B

FALL ARRESTERS ON ROPE

Sliding fall arrest system already mounted on its braided rope which makes it easy to set it up and follow-up for the user over a length 10 metres



Specific benefits



Ease of Use

- NFC system guarantees traceability

Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance

Certifications and norms



EN353-2
120 KG

Risk Protection



Fall



enjoy safety.

Edit 27/02/2026
www.deltaplus-usa.com



Fall protection

AN06410B

FALL ARRESTERS ON ROPE

Sliding fall arrest system already mounted on its braided rope which makes it easy to set it up and follow-up for the user over a length 10 metres

Standards - Details

Technical details

Type of equipment	Braided rope
Composition of the main support	Steel, Stainless steel, Polyamide
Max. length (m)	10
Length (m)	10
Maximum rope diameter (mm)	12
Maximum rope diameter (inch)	0.4716
Color	White-Black
Ending	1 loop sewn thimble
Weight (kg)	1,805
Maximum load for one person (kg)	120
Fall arrest work situations	Movement on lifeline, Long vertical movement or movement on inclined surface
Length (ft)	32.808



AN06410B

FALL ARRESTERS ON ROPE

Fall protection

Sliding fall arrest sytem already mounted on its braided rope which makes it easy to set it up and follow-up for the user over a length 10 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN06410B	White-Black	10 m	AN06410B	3295249309428	13295249309425	10	1	19.0 kg	23.0 cm	80.0 cm	32.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height