Fall protection

AN219CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks



Applications

- **Chemical Industry**
- **Automotive**
- **Oil & Gas (Extraction)**
- **Petrochemical**
- **Power Energy**

Certifications and norms

CE CATEGORY III

EN355
100 KG

Risk Protection

Fall

Fall protection

AN219CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	2
Width (inch)	1.0612
Width (mm)	27
Color	Yellow
Connector 1	Screw carabiner, steel, opening 18mm
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.6
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



坠落防护

504210

能量吸收带

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

物流信息

产品代码	颜色	尺码	六位码	条形码	箱码	箱规	最低销售	重量	箱长	箱宽	箱高
AN219CDD	黄色	2米	504210	3660348004572	13660348004579	5	1	8.04 kg	45.0 cm	29.5 cm	18.0 cm

箱规

最低销售

箱长

箱宽

箱高