



Fall protection

AN219CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks



Applications

- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Petrochemical
- Power Energy

Certifications and norms



EN355
100 KG

Risk Protection



Fall



Fall protection

AN219CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Polyester
Length (m)	2
Width (inch)	1.0612
Width (mm)	27
Color	Yellow
Connector 1	Screw carabiner, steel, opening 18mm
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.6
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616








Fall protection

AN219CDD

ENERGY ABSORBING LANYARDS

Fall arrest energy absorbing lanyard with wide webbing, connector and scaffold hooks

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN219CDD	Yellow	2 m	AN219CDD	3660348004572	13660348004579	5	1	8.04 kg	45.0 cm	29.5 cm	18.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height