



DSPIRIT2-MC S1P

CASUAL

Foot protection



Applications

- Public works
- Building
- Light industry
- Maintenance
- Automotive
- Public services

Certifications and norms



EN ISO 20345:2022
S1PS FO A E SR

Protects against risks



Antistatic



Heat



Shock



Slip



DSPIRIT2-MC S1P

CASUAL

Foot protection

Standards - Details

Technical details

Shoe type	High-cut shoe
Anti-perforation insert	Metal free
Size range	35 → 46



DSPIRIT2-MC S1P

CASUAL

Safety footwear

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
DSPIPSZ2BR035	Brown	35	DSPIRIT2-MC S1P	3295249640309	13295249640306	10	1	1.0 kg	0.325 m	0.65 m	0.28 m
DSPIPSZ2BR036	Brown	36	DSPIRIT2-MC S1P	3295249640316	13295249640313	10	1	1.0 kg	0.325 m	0.65 m	0.28 m
DSPIPSZ2BR037	Brown	37	DSPIRIT2-MC S1P	3295249640323	13295249640320	10	1	1.0 kg	0.325 m	0.65 m	0.28 m
DSPIPSZ2BR038	Brown	38	DSPIRIT2-MC S1P	3295249640330	13295249640337	10	1	1.0 kg	0.256 m	0.622 m	0.346 m
DSPIPSZ2BR039	Brown	39	DSPIRIT2-MC S1P	3295249640347	13295249640344	10	1	1.0 kg	0.26 m	0.626 m	0.352 m
DSPIPSZ2BR040	Brown	40	DSPIRIT2-MC S1P	3295249640354	13295249640351	10	1	1.0 kg	0.325 m	0.65 m	0.28 m
DSPIPSZ2BR041	Brown	41	DSPIRIT2-MC S1P	3295249640361	13295249640368	10	1	1.0 kg	0.26 m	0.626 m	0.348 m
DSPIPSZ2BR042	Brown	42	DSPIRIT2-MC S1P	3295249640378	13295249640375	10	1	1.0 kg	0.256 m	0.622 m	0.358 m
DSPIPSZ2BR043	Brown	43	DSPIRIT2-MC S1P	3295249640385	13295249640382	10	1	1.0 kg	0.365 m	0.65 m	0.3 m
DSPIPSZ2BR044	Brown	44	DSPIRIT2-MC S1P	3295249640392	13295249640399	10	1	1.0 kg	0.365 m	0.65 m	0.3 m
DSPIPSZ2BR045	Brown	45	DSPIRIT2-MC S1P	3295249640408	13295249640405	10	1	1.0 kg	0.365 m	0.65 m	0.3 m
DSPIPSZ2BR046	Brown	46	DSPIRIT2-MC S1P	3295249640415	13295249640412	10	1	1.0 kg	0.365 m	0.65 m	0.3 m



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height