



PROTECTOR LARGE AN181C20

RETRACTABLE FALL ARRESTERS

Fall protection



Specific benefits



Comfort

- Double swivel ensures it will maintain pursuit of user



Performance

- Certification above maximum rated load 100kg; product certified at 150kg



Ease of Use

- Carry handle for easy transport
- NFC system guarantees traceability



Sustainability

- Impact resistant ABS housing



Visibility

- Anti-fall visual indicator allows for instant verification that product is properly functioning

Applications

- Heavy Industry
- Light Industry
- Maintenance
- Automotive
- Oil & Gas (Extraction)
- Cleanliness

Certifications and norms



150 KG
150 KG (MAXIMUM RATED LOAD)
50 KG (MINIMUM NOMINAL LOAD)
F0 | USE: VERTICAL

Risk Protection



Fall



enjoy safety.

Edit 01/08/2026
www.deltaplus-usa.com



PROTECTOR LARGE AN181C20

RETRACTABLE FALL ARRESTERS

Fall protection

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS, Steel, Stainless steel
Max. length (m)	15
Min. length (m)	0,6
ARA lenght (m)	20
ARA lenght (inch)	787.402
Lock	Automatic system
Fall factor	F0
Cable diameter (mm) (mm)	4,5
Color	Black-Orange
Connector 1	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Lifespan from manufacturing (years)	20
Weight (kg)	15,50
Maximum load for one person (kg)	150
Type of conditioning	Sold by Unit
Fall arrest work situations	Long vertical movement or movement on inclined surface, Long horizontal movement on vertical structure
Locking system	Inertia locking system
Maximum rated load (kg)	150
Use of self retracting	Vertical



PROTECTOR LARGE AN181C20

RETRACTABLE FALL ARRESTERS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN181C20	Black-Orange	20 m	PROTECTOR LARGE AN181C20	3295249324148	100000000000007	1	1	11.8 kg	47.0 cm	28.0 cm	20.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height