AN181C06

RETRACTABLE FALL ARRESTERS

Fall protection



Certifications and norms

Risk Protection

Fall

Specific benefits

Comfort

· Double swivel ensures it will maintain pursuit of user

Performance

· Certification above maximum rated load 100kg: product certified at 150kg

Ease of Use

· Carry handle for easy transport
· NFC system guarantees traceability

Sustainability

· Impact resistant ABS housing

Visibility

· Anti-fall visual indicator allows for instant verification that product is properly functioning

Applications

- **Heavy Industry**
- **Light Industry**
- **Maintenance**
- **Automotive**
- **Oil & Gas (Extraction)**
- **Cleanliness**

Fall protection

AN181C06

RETRACTABLE FALL ARRESTERS

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS, Steel, Stainless steel
Max. length (m)	6
Min. length (m)	0.6
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Lock	Automatic system
Fall factor	F0
Cable diameter (mm) (mm)	5
Color	Black-Orange
Connector 1	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Lifespan from manufacturing (years)	20
Maximum load for one person (kg)	150
Type of conditioning	Sold by Unit
Use	For vertical movement
Fall arrest work situations	Long vertical movement or movement on inclined surface, Long horizontal movement on vertical structure
Locking system	Inertia locking system
Maximum breaking load (kg)	150
Use of self retracting	Vertical

AN181C06

RETRACTABLE FALL ARRESTERS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
SRLPROC006Z1BK	Black-Orange	6 m	AN181C06	3295249644239	13295249644236	1	1	1.0 kg	1.0 m	1.0 m	1.0 m

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height