



Fall protection

MEDBLOC AN108S06

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres



Specific benefits



Ease of Use

- NFC system guarantees traceability



Sustainability

- Impact resistant ABS housing



Visibility

- Anti-fall visual indicator allows for instant verification that product is properly functioning

Certifications and norms



130 KG
130 KG (MAXIMUM RATED LOAD)
50 KG (MINIMUM NOMINAL LOAD)
F0 | USE: VERTICAL

Applications

- Building
- Finishing Works/Craftsmanship
- Manufacturing/Transformation
- Light Industry
- Maintenance

Risk Protection



Fall



enjoy safety.

Edit 07/09/2026
www.deltaplus-usa.com



Fall protection

MEDBLOC AN108S06

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Webbing reel
Composition of the main support	ABS, Steel, Polyester
Max. length (m)	6
Strap width (mm)	25
Min. length (m)	0,6
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Lock	Automatic system
Fall factor	F0
Included elements	Energy absorber
Color	Black
Connector 1	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Lifespan from manufacturing (years)	10
Weight (kg)	2.24
Maximum load for one person (kg)	130
Type of conditioning	Sold by Unit
Fall arrest work situations	Long vertical movement or movement on inclined surface, Long horizontal movement on vertical structure
Locking system	Inertia locking system
Maximum rated load (kg)	130
Use of self retracting	Vertical



Fall protection

MEDBLOC AN108S06

RETRACTABLE FALL ARRESTERS

Self-retractable webbing fall arrester for vertical and horizontal use, for distances of up to 6 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN108S06	Black	6 m	MEDBLOC AN108S06	3295249324025	13295249324022	5	1	12.7 kg	49.5 cm	22.0 cm	21.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height