



Hand protection

VENICUTD02

LONG-LASTING CUT WORK

A4 rated HEATnocut latex coated gloves for contact heat and cut resistance



Specific benefits



Performance

- The high-performance HEATnocut fiber provides excellent abrasion and cut resistance
- The high-performance HEATnocut fiber provides resistance to contact heat (250° for 15 seconds)

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Mining
- Temporary Work
- Power Energy

Certifications and norms



EN 388
3 X 4 2 D



EN 407
X 2 X X X X



A4 X X

Risk Protection



Heat



Cutting



Wearing



enjoy safety.

Edit 12/04/2026
www.deltaplus-usa.com



Hand protection

VENICUTD02

LONG-LASTING CUT WORK

A4 rated HEATnocut latex coated gloves for contact heat and cut resistance

Standards - Details



EN388:2016+A1:2018

- 3 [0-4] ABRASION RESISTANCE
- X [0-5] CUT RESISTANCE
- 4 [0-4] TEAR RESISTANCE
- 2 [0-4] PIERCE RESISTANCE
- D [A-F] CUT RESISTANCE ISO 13997



EN 407

- X [0-4] BURNING BEHAVIOUR
- 2 [0-4] CONTACT HEAT RESISTANCE
- X [0-4] CONVECTIVE HEAT
- X [0-4] RADIANT HEAT RESISTANCE
- X [0-4] SMALL DROP MOLTEN METAL
- X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Mechanical glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Fiber	HEATnocut
Coating Level	Palm Coating
Coating Material	Latex
Coating Finish	Grip-textured
Number of Coatings	Single Coated
Gauge	10
Benefits element	Reach, Vendor pack
Color	Yellow-Grey-Black
Size	7, 8, 9, 10
Type of conditioning	in individual bags








Safety gloves

VENICUTD02

LONG-LASTING CUT WORK

Level D cut-resistant glove with very good thermal resistance, ideal in wet conditions

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUTD02GJ08	Yellow-Grey-Black	08	VENICUTD02	3295249158484	13295249158481	60	12	8.3 kg	30.0 cm	38.2 cm	46.0 cm
VECUTD02GJ09	Yellow-Grey-Black	09	VENICUTD02	3295249150785	13295249150782	60	12	9.2 kg	29.8 cm	46.4 cm	43.8 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height