Hand protection

CA615K

THERMAL WELDING WORKS

Thermal leather glove, offers increased durability in the heavy industry thanks to their Kevlar stitching



Specific benefits

Performance

· Extra thick and long for extra protection of the entire arm
· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- **Public Works**
- **Building**
- **Finishing Works/Craftsmanship**
- **Maintenance**
- **Automotive**
- **Mining**

Certifications and norms

CE CATEGORY II

EN 388
3 1 3 2 X

EN 12477
TYPE A

EN 407
4 1 3 X 4 X

Risk Protection

Heat

Hand protection

CA615K

THERMAL WELDING WORKS

Thermal leather glove, offers increased durability in the heavy industry thanks to their Kevlar stitching

Standards - Details



EN388:2016+A1:2018
3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
3 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997



EN 407
THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
3 [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Welding glove
Mechanical Glove Type	Cut Sewn
Special gloves kind	Welding
Thickness (mm)	1,2 -> 1,4
Arm level protection	Forearm cuff (< 400mm)
Cuff caracteristic	Leather cuff
Benefits element	Kevlar stitching
Color	Red
Size	10
Type of conditioning	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
60 pairs /box

Safety gloves

CA615K

THERMAL WELDING WORKS

Thermal leather glove, offers increased durability in the heavy industry thanks to their Kevlar stitching

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
CA615K10	Red	10	CA615K	3295249021597	13295249021594	60	12	22.1 kg	26.2 cm	37.0 cm	77.6 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height