



WFB159

WORKS IN DRY ENVIRONMENT

Hand protection



Applications

- Public Works
- Building
- Maintenance
- Automotive
- Temporary Work
- Storage

Certifications and norms



EN 388
2122X

Risk Protection



Wearing



WFB159

WORKS IN DRY ENVIRONMENT

Hand protection

Standards - Details



EN388:2016+A1:2018

2 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical Glove Type	Cut Sewn
Thickness (mm)	0.8
Arm level protection	Standard cuff (< 290mm)
Cuff characteristic	Sewn open cuff with elastic
Color	Natural
Size	9, 10
Type of conditioning	Bulk bag of 12








WFB159

WORKS IN DRY ENVIRONMENT

Safety gloves

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WFB15909	Natural	09	WFB159	3295249280994	13295249280991	120	12	0.0 kg	0.0 cm	0.0 cm	0.0 cm
WFB15910	Natural	10	WFB159	3295249281007	13295249281004	120	12	0.0 kg	0.0 cm	0.0 cm	0.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height