WFB159

WORKS IN DRY ENVIRONMENT

Hand protection



Applications

- Public Works
- Building
- Maintenance
- Automotive
- Temporary Work
- Storage

Certifications and norms

CE CATEGORY II

EN 388
2 1 2 2 X

Risk Protection

Wearing

WFB159

WORKS IN DRY ENVIRONMENT

Hand protection

Standards - Details



EN388:2016+A1:2018
2 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical Glove Type	Cut Sewn
Thickness (mm)	0.8
Arm level protection	Standard cuff (< 290mm)
Cuff caracteristic	Sewn open cuff with elastic
Color	Natural
Size	9, 10
Type of conditioning	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
120 pairs /box



手部防护

204160

干燥环境工作

皮革防护手套全牛皮款，六价铬含量＜0.6 ppm，美式截面，翼状拇指，弹性掌背，透气

物流信息

产品代码	颜色	尺码	六位码	条形码	箱码	箱规	最低销售	重量	箱长	箱宽	箱高
WFB15909	自然色	09	204160	3295249280994	13295249280991	120	12	0.0 kg	0.0 cm	0.0 cm	0.0 cm
WFB15910	自然色	10	204160	3295249281007	13295249281004	120	12	0.0 kg	0.0 cm	0.0 cm	0.0 cm

箱规

最低销售

箱长

箱宽

箱高