EOS NOCUT WINTER VV913

长时间正常切割作业

手部防护

D级防切割手套，防寒防冲击，适用于水性或油性环境中的多用途作业



具体优势

耐用性

· 双涂层具有卓越的耐磨性，使用寿命更长

易用性

· 完美的贴合性，使用户在长时间使用我们的手套时不会感到手腕部位的任何不适

· 尼龙搭扣设计，给手腕提供更好收紧保护

卫生环保

· 可清洗手套，可重复使用

高性能

· 灵活性加强，提升对冲击和挤压的防护

· 丁腈涂层让使用者在油腻的环境中工作时，对接触物具备良好的抓握力

标准和认证

CE 2类

EN 388
4 X 4 4 D P

EN 511
1
3
X

EN 407
X 1 X X X X

A4 X X

技术与标签

0% DMF 无DMF

0% SILICONE 无硅

应用行业

- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 化工业
- 汽车业

防范风险

冲击 切割 寒冷 磨损

DELTAPLUS

enjoy safety

编辑 26/11/2026

www.deltaplus.com.cn

EOS NOCUT WINTER VV913

长时间正常切割作业

手部防护

D级防切割手套，防寒防冲击，适用于水性或油性环境中的多用途作业

详细信息 - 标准



EN388:2016+A1:2018
4 [0-4] 耐磨
X [0-5] 防切割
4 [0-4] TEAR RESISTANCE
4 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997
P [P] IMPACT RESISTANCE (OPTIONAL)



EN 407
X [0-4] 燃烧性能
1 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

技术细节

手套类别	特殊手套
手套类别	抗冲击手套
机械手套类	针织
特殊手套类型	防寒, 防冲击
涂层水平	掌面涂层
涂层材质	丁腈
涂层饰面	光滑涂层, 抓纹涂层, 双涂层
涂层数	双涂层
袖口特征	魔术贴袖口
产品优势	Reach, 供应商包装, 凯夫拉缝线
颜色	黄色-灰色-黑色
尺码	8, 9, 10, 11
包装类型	标题卡

包装

销售单位: 标题卡
60 成对/箱

Safety gloves

EOS NOCUT WINTER VV913

LONG-LASTING CUT WORK

Level D cut, winter impact-resistant glove, ideal for multipurpose work in aqueous or oily environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VV913JA09	Yellow-Grey-Black	09	EOS NOCUT WINTER VV913	3295249233068	13295249233065	60	6	17.1 kg	33.6 cm	71.2 cm	35.8 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height