手部防护

VENICUTD08

长时间正常切割作业

D 级防割手套，干燥环境下的理想选择



具体优势

高性能

· 聚氨酯涂层的防滑性能提供了良好的抓握力。

高性价比

· 人性化包装规格，3副装正好适用1周

应用行业

- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 汽车业
- 采矿

标准和认证

CE 2类

EN 388
4 X 4 2 D

A4 X X

防范风险

切割

磨损

手部防护

VENICUTD08

长时间正常切割作业

D 级防割手套，干燥环境下的理想选择

详细信息 - 标准

EN388:2016+A1:2018
4 [0-4] 耐磨
X [0-5] 防切割
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997

技术细节

手套类别	机械防护手套
手套类别	针织涂层手套
机械手套类	针织
纬纱	Econocut
涂层水平	掌面涂层
涂层材质	PU
涂层饰面	光滑涂层
涂层数	单涂层
针数	13
产品优势	Reach, 供应商包装
颜色	灰色
尺码	7, 8, 9, 10, 11
包装类型	3/包

包装

销售单位: 3/包
可订购多个聚乙烯袋: 4 袋 3 对
120 成对/箱

Safety gloves

VENICUTD08

LONG-LASTING CUT WORK

Level D cut-resistant glove, ideal in dry conditions

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUTD08GRG307	Grey	07	VENICUTD08	3295249192037	13295249192034	40	4	10.08 kg	31.0 cm	62.0 cm	34.0 cm
VECUTD08GRG308	Grey	08	VENICUTD08	3295249192044	13295249192041	40	4	11.03 kg	31.0 cm	62.0 cm	34.0 cm
VECUTD08GRG309	Grey	09	VENICUTD08	3295249192051	13295249192058	40	4	11.85 kg	31.0 cm	65.0 cm	35.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height