



手部防护

VENICUTD03

长时间正常切割作业

D 级触感防割手套，兼具舒适性和精细度，是油性或水性环境下的理想选择



具体优势

易用性

· 可触屏，用户在使用平板电脑或智能手机时，无需摘下手套

卫生环保

· 由于其良好的透气性，减少出汗
· 丁腈涂层，使用者无过敏风险

高性能

· 重量非常轻，使其具备最佳的灵巧性
· 丁腈涂层让使用者在油腻的环境中工作时，对接触物具备良好的抓握力

兼容性

· 支持触屏使用

技术与标签




触摸屏

应用行业

- 公共工程
- 建筑业
- 终饰工程/工艺
- 维修业
- 汽车业
- 采矿

标准和认证



防范风险



切割



磨损



enjoy safety



手部防护

VENICUTD03

长时间正常切割作业

D 级触感防割手套，兼具舒适性和精细度，是油性或水性环境下的理想选择

详细信息 - 标准



EN388:2016+A1:2018

4 [0-4] 耐磨

X [0-5] 防切割

4 [0-4] TEAR RESISTANCE

3 [0-4] PIERCE RESISTANCE

D [A-F] CUT RESISTANCE ISO 13997

技术细节

手套类别	机械防护手套
手套类别	针织涂层手套
机械手套类	针织
纬纱	DELTAnocut
涂层水平	掌面涂层
涂层材质	丁腈
涂层饰面	抓纹涂层
涂层数	单涂层
针数	15
袖口特征	加长袖口
袖口长度 (mm)	100
产品优势	触摸感应, Reach, 供应商包装, 长袖口 (>290mm)
颜色	灰色-黑色
尺码	7, 8, 9, 10
包装类型	独立包装








Safety gloves

VENICUTD03

LONG-LASTING CUT WORK

Tactile level D cut-resistant glove combining comfort and finesse of work, ideal in oily or aqueous environments

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUTD03GR08	Grey-Black	08	VENICUTD03	3295249196059	13295249196056	60	12	5.0 kg	18.8 cm	30.6 cm	68.4 cm
VECUTD03GR09	Grey-Black	09	VENICUTD03	3295249196066	13295249196063	60	12	5.5 kg	30.0 cm	68.0 cm	19.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height