



Hand protection

CA515R

THERMAL WELDING WORKS

Thermal leather glove, suitable for welding work owing to its resistance to contact heat



Specific benefits



Performance

- Extra thick and long for extra protection of the entire arm
- The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Mining

Certifications and norms



EN 388
3 1 3 2 X

EN 12477
TYPE A



EN 407
4 1 3 X 4 X

Risk Protection



Heat



enjoy safety.

Edit 12/07/2026
www.deltaplus-usa.com



Hand protection

CA515R

THERMAL WELDING WORKS

Thermal leather glove, suitable for welding work owing to its resistance to contact heat

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
3 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997



EN 407

THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
3 [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Welding glove
Mechanical Glove Type	Cut Sewn
Thickness (mm)	1,2 -> 1,4
Arm level protection	Forearm cuff (< 400mm)
Cuff characteristic	Leather cuff
Color	Red
Size	10
Type of conditioning	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
60 pairs /box



Safety gloves

CA515R

THERMAL WELDING WORKS

Thermal leather glove, suitable for welding work owing to its resistance to contact heat

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
CA515R10	Red	10	CA515R	3295249025939	13295249025936	60	12	22.9 kg	26.6 cm	36.4 cm	77.2 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height