



Fall protection

LV102100

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 1m



Specific benefits



Sustainability

· High webbing tenacity thanks to its weave and width

Applications

- Agriculture
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)

Certifications and norms



EN354

EN 795
TYPE B

Risk Protection



Fall



Fall protection

LV102100

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 1m

Standards - Details

Technical details

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Steel, Polyester
Length (m)	1
Width (inch)	1.7685
Width (mm)	45
Color	Black-Orange
Ending	Loop with shrinkage
Lifespan from manufacturing (years)	10
Weight (kg)	0,222
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	3.2808



Fall protection

LV102100

ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 1m

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LV102100	Black-Orange	1 m	LV102100	3660348006316	13660348006313	15	1	4.34 kg	44.0 cm	28.0 cm	15.0 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height