Fall protection

SPIRAL AN218S200ADD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.



Specific benefits

Hygiene

· Can wash harnesses and textiles with neutral soap

Performance

· Certification above maximum rated load 100kg: product certified at 140kg

· Webbing with better abrasion resistance and certified against sharp edges

Sustainability

· Heat shrinking sleeve extends the life of the lanyard

Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Applications

- **Public Works**
- **Finishing Works/Craftsmanship**
- **Automotive**
- **Power Energy**
- **Storage**

Risk Protection

Fall

Fall protection

SPIRAL AN218S200ADD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.

Standards - Details

Technical details

Type of equipment	Braided rope lanyard with thermoformable sheath
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Rope diameter (mm)	10,5
With connector	yes
Color	White-Black
Connector 1	Automatic lock hook, steel, opening 19mm
Benefits element	Leading edge
Ending	2 sewn thimble loops
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,97
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616

Fall protection

SPIRAL AN218S200ADD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN218S200ADD	White-Black	2 m	SPIRAL AN218S200ADD	3295249265113	13295249265110	5	1	10.8 kg	29.4 cm	45.6 cm	27.4 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height