坠落防护

SPIRAL AN218S200ADD

能量吸收带

坠落防护/AN218S200ADD/代尔塔产品优势



具体优势

卫生环保

· 系带和织物面料可用中性肥皂洗涤

高性能

· 认证的最大额定负载在100kg以上：产品认证在140kg以下

· 系带的耐磨性增强，通过可在锐物边缘使用的认证

耐用性

· 热性可收缩保护套，延长绳索的使用寿命

标准和认证

CE 3类

EN355
水平认证 - 140 KG
RFU 11.062
140 KG

应用行业

- 公共工程
- 终饰工程/工艺
- 汽车业
- 电力能源
- 仓储

防范风险

坠落

坠落防护

SPIRAL AN218S200ADD

能量吸收带

坠落防护/AN218S200ADD/代尔塔产品优势

详细信息 - 标准

技术细节

装备类型	带热成型套的编织绳
主要支架的组成	钢, 玻璃纤维, 支撑材料/聚酯纤维
长度 (m)	2
绳索直径 (mm)	10,5
带有连接器	是
颜色	白色-黑色
连接器 (用户方)	小钩，钢制，开口19mm
产品优势	前缘
终端件	2个缝制套环
连接器 (结构方)	2 个自动锁钩，钢质，开口 55 毫米
自生产之日起的产品寿命 (年)	10
重量 (kg)	1,97
防坠落作业类型	生命线上的移动, 短距离垂直移动或倾斜表面上的移动（小于3米），短距离水平移动 (小于3米), 具有多重连接/断开功能的长距离移动
长度 (ft)	6.5616

Fall protection

SPIRAL AN218S200ADD

ENERGY ABSORBING LANYARDS

Compact, 2-metre double energy-absorbing lanyard with patented system, guaranteeing great freedom of movement for short distances.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN218S200ADD	White-Black	2 m	SPIRAL AN218S200ADD	3295249265113	13295249265110	5	1	10.8 kg	29.4 cm	45.6 cm	27.4 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height