Fall protection

AN245200ADD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Risk Protection

Fall

Specific benefits

Comfort

· Elastic webbing lanyard for easy movement and safety

Hygiene

· Can wash harnesses and textiles with neutral soap

Performance

· Certification above maximum rated load 100kg: product certified at 140kg
· Webbing with better abrasion resistance and certified against sharp edges

Ease of Use

· Automatic carabiners for secure locking and time saving
· NFC system guarantees traceability

Applications

- **Public Works**
- **Finishing Works/Craftsmanship**
- **Chemical Industry**
- **Automotive**
- **Oil & Gas (Extraction)**
- **Mining**

Fall protection

AN245200ADD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black-Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 thimble ferrule loops
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Weight (kg)	1,67
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616

坠落防护

504240

能量吸收带

双大钩弹力减震绳，由很轻的弹性织带制成，保证移动自由

物流信息

产品代码	颜色	尺码	六位码	条形码	箱码	箱规	最低销售	重量	箱长	箱宽	箱高
AN245200ADD	黑色-橙色	1.40到2米	504240	3295249265137	13295249265134	5	1	9.9 kg	29.2 cm	18.2 cm	44.6 cm

箱规

最低销售

箱长

箱宽

箱高