Fall protection

AN235200AD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Risk Protection

Fall

Specific benefits

Hygiene

· Can wash harnesses and textiles with neutral soap

Performance

· Certification above maximum rated load 100kg: product certified at 140kg
· Webbing with better abrasion resistance and certified against sharp edges

Ease of Use

· Automatic carabiners for secure locking and time saving
· NFC system guarantees traceability

Applications

- **Public Works**
- **Finishing Works/Craftsmanship**
- **Chemical Industry**
- **Automotive**
- **Oil & Gas (Extraction)**
- **Mining**

Fall protection

AN235200AD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Black-Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Weight (kg)	1,07
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616

AN235200AD

ENERGY ABSORBING LANYARDS

Fall protection

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN235200AD	Black-Orange	1.40 → 2 m	AN235200AD	3295249265120	13295249265127	5	1	6.104 kg	28.8 cm	43.2 cm	14.8 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height