



Fall protection

# LV102050

## ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m



### Specific benefits



#### Sustainability

· High webbing tenacity thanks to its weave and width

### Applications

- Agriculture
- Finishing Works/Craftsmanship
- Chemical Industry
- Automotive
- Oil & Gas (Extraction)
- Mining

### Certifications and norms



CATEGORY III

EN354

EN 795  
TYPE B

### Risk Protection



Fall



*enjoy safety.*



Fall protection

# LV102050

## ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m

### Standards - Details

### Technical details

Type of equipment	Extension strap in high tenacity polyester with D-ring.
Composition of the main support	Steel, Polyester
Strap width (mm)	45mm
Length (m)	0,5
Width (inch)	1.7685
Width (mm)	45
Color	Black-Orange
Ending	Loop with shrinkage
Weight (kg)	0,300
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)
Lenght (ft)	1.6404








Fall protection

# LV102050

## ANCHORAGE DEVICES

Anchorage strap that can also be used as an evacuation strap, to be connected to the harness's D-ring - 0,5m

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LV102050	Black-Orange	0,50 m	LV102050	3295249204631	13295249204638	15	1	3.6 kg	31.0 cm	22.0 cm	16.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height