



Fall protection

LO147150

LANYARDS

1.5 metre double, braided rope lanyard with thimble loop ends for maximum versatility



Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)
- Mining

Certifications and norms



EN354

Risk Protection



Fall



Fall protection

LO147150

LANYARDS

1.5 metre double, braided rope lanyard with thimble loop ends for maximum versatility

Standards - Details

Technical details

Type of equipment	Braided rope lanyard
Composition of the main support	Polyamide
Length (m)	1,5
Rope diameter (mm)	10,5
Cable diameter (mm) (mm)	10,5
Color	White
Ending	2 sewn thimble loops
Weight (kg)	0,264
Fall arrest work situations	Restraint
Lenght (ft)	4.9213








Fall protection

LO147150

LANYARDS

1.5 metre double, braided rope lanyard with thimble loop ends for maximum versatility

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
LO147150	White	1.50 m	LO147150	3660348006293	13660348006290	15	1	5.1 kg	22.0 cm	48.0 cm	21.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height