Fall protection

AN209CC

ENERGY ABSORBING LANYARDS

Fall arrester with energy absorber



Specific benefits

Hygiene

· Can wash harnesses and textiles with neutral soap

Ease of Use

· NFC system guarantees traceability

Sustainability

· High webbing tenacity thanks to its weave and width

Compatibility

· Compatible with all kind of harnesses

Certifications and norms

CE CATEGORY III

EN355
100 KG

Applications

- **Chemical Industry**
- **Automotive**
- **Petrochemical**

Risk Protection

Fall

Fall protection

AN209CC

ENERGY ABSORBING LANYARDS

Fall arrester with energy absorber

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Polyester
Length (m)	2
With connector	yes
Color	Yellow-Black
Connector 1	Screw carabiner, steel, opening 18mm
Ending	1 loop sewn thimble
Connectors (structure side)	Screw carabiner, steel, opening 18mm
Weight (kg)	1
Type of conditioning	box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616

Fall protection

AN209CC

ENERGY ABSORBING LANYARDS

Fall arrester with energy absorber

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN209CC	Yellow-Black	-	AN209CC	3660348004565	13660348004562	5	1	3.5 kg	38.5 cm	23.5 cm	17.5 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height