



# AN209CD

## ENERGY ABSORBING LANYARDS

Fall protection

### Applications

- Chemical Industry
- Automotive
- Petrochemical



### Certifications and norms



EN355  
100 KG

### Risk Protection



Fall



# AN209CD

## ENERGY ABSORBING LANYARDS

Fall protection

### Standards - Details

### Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Polyamide, Polyester
Length (m)	2
Color	Yellow-Black
Connector 1	Screw carabiner, steel, opening 18mm
Connectors (structure side)	1 automatic lock hook, steel, opening 55mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Length (ft)	6.5616



# AN209CD

## ENERGY ABSORBING LANYARDS

Fall protection

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN209CD	Yellow-Black	-	AN209CD	3660348004701	13660348004708	5	1	5.0 kg	38.5 cm	23.5 cm	17.5 cm

Multiple sales

Minimum sales

Box Width

Box Depth

Box Height